

Inch Series Taper Roller Bearing

select	Inquiry	Bearing No.	Boundary dimensions [mm]			Basic load ratings(kN)		Pu	Limiting speed(rpm)		Weight Kg
			d	D	T	Dynamic(Cr)	Static(Cor)		Speed Ratings	Limiting Speed	
687/672	101.6	168.275	41.275	233	365	39	2800	4000	3.45		
37425/2/37625/2/Q	107.95	158.75	23.02	101	163	18.3	2800	4300	1.4		
64450/64700	114.3	177.8	41.275	251	415	42.5	2600	3800	3.6		
68450/68712	114.3	180.975	34.925	183	280	30	2600	3800	2.95		
48290/48220/Q	127	182.562	39.688	229	440	44	2400	3600	3.3		
67388/67322	127	196.85	46.038	319	585	60	2200	3400	5.2		
L327249/210	133.35	177.008	25.4	134	280	28	2400	3600	1.8		
67391/67322	133.35	196.85	46.038	319	585	60	2200	3400	4.8		
HM231132/110	139.7	236.538	57.15	512	850	86.5	1900	2800	10		
HM231148/110	149.225	236.538	57.15	512	850	86.5	1900	2800	10		
L432348/310	158.75	205.583	23.812	138	280	27	2000	3000	1.95		
L432349/310	158.75	205.583	23.812	138	280	27	2000	3000	1.95		
36990/36920	177.8	227.012	30.162	187	425	40	1800	2800	3		
M336948/912	178.595	265.112	51.595	495	880	86.5	1700	2400	9.6		
M336949/912	179.934	265.112	51.595	495	880	86.5	1700	2400	9.4		
87737/87111	187.325	282.575	50.8	402	695	67	1600	2200	9.8		
M239449/410	190.475	279.4	52.388	523	980	95	1600	2200	9.5		
87750/87111	190.5	282.575	50.8	402	695	67	1600	2200	9.6		
M239448A/410	191.237	279.4	52.388	523	980	95	1600	2200	9.2		
LL639249/210	196.85	241.3	23.812	154	315	29	1700	2600	2		
LL639249/2/210/4	196.85	241.3	23.812	154	315	29	1700	2600	2		
LM739749/710/VE174	196.85	257.175	39.688	275	655	58.5	1600	2400	5.3		
LM241147/110/QVQ051	200.025	276.225	42.862	450	780	72	1700	2200	7.7		
LM241148/110/QVQ051	203.987	276.225	42.862	450	780	72	1700	2200	7.25		
LM742749/710/VE174	215.9	285.75	46.038	380	850	76.5	1500	2200	7.9		
LM742747/710	216.408	285.75	46.038	380	850	76.5	1500	2200	7.85		
LM742747A/710	216.713	285.75	46.038	380	850	76.5	1500	2200	7.85		
LM245846/810	230.188	317.5	47.625	523	980	90	1300	2000	10.5		
544091/2B/544118A/2B	231.775	300.038	33.338	216	425	39	1400	2000	5.3		
LM245848/810	231.775	317.5	47.625	523	980	90	1300	2000	10.5		