

双列圆柱滚子轴承

轴承型号	尺寸 (mm)			基本额定负载 (KN)		重量 (kg)
	d	D	B	(Cr)	(Cor)	
NN3034K/W33	170	260	67	470	860	12.9
1-2029	170	306	278	1650	2690	67.2
NN3034K/C9	170	260	67	470	860	12.9
NN3034	170	260	67	470	860	13.3
NNU4132X3	160	265	120	1060	1990	29
NN3034K	170	260	67	470	860	12.9
NN3032	160	240	60	380	675	8.38
NN3032K/W33	160	240	60	380	675	8.38
NN3030K/W33	150	225	56	363	650	7.7
NN3032K	160	240	60	380	675	8.39
NN3030/C9	150	225	56	363	650	7.75
NN3030	150	225	56	363	650	7.75
NN3030K	150	225	56	363	650	7.7
NN3030/YA8	150	225	56	363	650	7.75
NN3028K/W33	140	210	53	320	575	6
NN3028	140	210	53	320	575	6.05
NN3028K/C9	140	210	53	320	575	6.05
NN3028KTN1	140	210	53	320	575	5.76
NN3028K	140	210	53	320	575	6.05
NNU3028/C9W33	140	210	53	320	575	6.18
NNFP3326X3	130	300	172.644	1360	2870	74.7
NNJ4928	140	190	50	199	405	4.19
NN3026K/W33	130	200	52	305	530	5.35
NN3026K	130	200	52	305	530	5.34
NNTR120-2Z	120	290	133	968	1600	50.9
NN3026	130	200	52	305	530	5.54

双列圆柱滚子轴承

NN3024	120	180	46	243	445	3.86
NN3024K	120	180	46	243	445	3.85
NN3022	110	170	45	220	405	3.74
NNU622Q1/HCYA7	110	225	150	950	1460	28