

单排四点角接触球式回转支承

型号		外形尺寸 mm						轴径				结构尺寸					齿轮参数			外齿		内齿		额定载 荷	重量
无齿型	外齿型	内齿型	d	D	H	D1	D2	dn1 dn2	dm1 dm2	L	n	n1	D1	d1	H1	h	b	m	Da	z	da	z	Coa KN	kg	
010.20.200	011.20.200		280	120	60	248	152	16	M14	28	12	2	201	199	50	10	40	3	300	98					
010.20.224	011.20.224		304	144	60	272	176	16	M14	28	12	2	225	223	50	10	40	3	312	105					
010.20.250	011.20.250		330	170	60	298	202	16	M14	28	18	2	251	249	50	10	40	4	352	86					
010.20.280	011.20.280		360	200	60	328	232	16	M14	28	18	2	281	279	50	10	40	4	348	94					
010.25.315	011.25.315	013.25.315	408	222	70	372	258	18	M16	32	20	2	316	314	60	10	50	5	435	85	190	40			
010.25.355	011.25.355	013.25.355	448	262	70	412	298	18	M16	32	20	2	356	354	60	10	50	5	475	93	235	49			
010.25.400	011.25.400	013.25.400	493	307	70	457	343	18	M16	32	24	2	401	399	60	10	50	6	528	86	276	48			
010.25.450	011.25.450	013.25.450	543	357	70	507	393	18	M16	32	24	2	451	449	60	10	50	6	576	94	324	56			
010.30.500	011.30.500	013.30.500	602	398	80	566	434	18	M16	32	20	4	501	498	70	10	60	5	629	123	367	74	1290	75.8	
010.30.500	012.30.500	014.30.500	602	398	80	566	434	18	M16	32	20	4	501	498	70	10	60	6	629	102	368	62	1290	75.8	
010.25.500	011.25.500	013.25.500	602	398	80	566	434	18	M16	32	20	4	501	499	70	10	60	5	628	123	367	74	1290	75.8	
010.25.500	012.25.500	014.25.500	602	398	80	566	434	18	M16	32	20	4	501	499	70	10	60	6	629	102	368	62	1290	75.8	
010.30.560	011.30.560	013.30.560	662	458	80	626	494	18	M16	32	20	4	561	558	70	10	60	5	689	135	427	86	1440	94	
010.30.560	012.30.560	014.30.560	662	458	80	626	494	18	M16	32	20	4	561	558	70	10	60	6	689	112	428	72	1440	94	
010.25.560	011.25.560	013.25.560	662	458	80	626	494	18	M16	32	20	4	561	559	70	10	60	5	689	135	427	86	1440	94	
010.25.560	012.25.560	014.25.560	662	458	80	626	494	18	M16	32	20	4	561	559	70	10	60	6	689	112	428	72	1440	94	
010.30.630	011.30.630	013.30.630	732	528	80	696	564	18	M16	32	24	4	631	628	70	10	60	6	773	126	494	83	187	110	
010.30.630	012.30.630	014.30.630	732	528	80	696	564	18	M16	32	24	4	631	628	70	10	60	8	774	94	491	62	187	110	
010.25.630	011.25.630	013.25.630	732	528	80	696	564	18	M16	32	24	4	631	629	70	10	60	6	773	126	494	83	187	110	
010.25.630	012.25.630	014.25.630	732	528	80	696	564	18	M16	32	24	4	631	629	70	10	60	8	774	94	491	62	187	110	
010.30.710	011.30.710	013.30.710	812	608	80	776	644	18	M16	32	24	4	711	708	70	10	60	6	851	139	572	96	2120	120	
010.30.710	012.30.710	014.30.710	812	608	80	776	644	18	M16	32	24	4	711	708	70	10	60	8	854	104	571	72	2120	120	
010.25.710	011.25.710	013.25.710	812	608	80	776	644	18	M16	32	24	4	711	709	70	10	60	6	851	139	572	96	2120	120	
010.25.710	012.25.710	014.25.710	812	608	80	776	644	18	M16	32	24	4	711	709	70	10	60	8	854	104	571	72	2120	120	
010.40.800	011.40.800	013.40.800	922	678	100	878	722	22	M20	40	30	6	801	798	90	10	80	8	966	118	635	80	3130	256	
010.40.800	012.40.800	014.40.800	922	678	100	878	722	22	M20	40	30	6	801	798	90	10	80	10	968	94	634	64	3130	256	
010.30.800	011.30.800	013.30.800	922	678	100	878	722	22	M20	40	30	6	801	798	90	10	80	8	966	118	635	80	3130	256	
010.30.800	012.30.800	014.30.800	922	678	100	878	722	22	M20	40	30	6	801	798	90	10	80	10	968	94	634	64	3130	256	
010.40.900	011.40.900	013.40.900	1022	778	100	978	822	23	M21	40	30		901	898				8	1062	130	739	93	3550	240	
010.40.900	012.40.900	014.40.900	1022	778	100	978	822	24	M22	40	30		901	898				10	1068	104	734	74	3550	240	

Page : 1/1